

HS-AS Studs

isolation



Provides a barrier to cut down on electrical interference.

Mounting Studs provide a secure, permanent or semi-permanent point of connection.

Up to a maximum temperature range of 284°F.

Part No.	Connection Point 1	Connection Point 2	
HS-AS046-1	M6 x 1 Female	M6 x 1 Male	
HS-AS046-2	1/4"-28 UNF Female	1/4"-28 UNF Male	
HS-AS046-3	M8 x 1.25 Female	M8 x 1.25 Male	
HS-AS051-1/4	1/4"-28 UNF Male	1/4" - 28UNF Female Nylatron	
HS-AS051-M6	M6 x 1 Male	M6 x 1 Female Nylatron	
HS-AS051-M8	M8 x 1.25 Male	M8 x 1.25 Female Nylatron	
HS-AS051-M8X1.25	M8 x 1.00 Male	M8 x 1.25 Female Nylatron	
HS-AS051-M10	M10 x 1.5 Male	M10 x 1.5 Female Nylatron	
HS-AS051-M10X1.25	M10 x 1.25 x 10mm Male	M10 x 1.25 Female Nylatron	










www.ie-central.com

We reserve the right to alter the specification of this product without prior notice
TS1443U



HS-AS Studs

isolation

Part No.	Connection			
HS-AS061-1/4	1/4"-28 UNF Male	1/4" - 28UNF Female Peek		
HS-AS061-M6	M6 x 1 Male	M6 x 1 Female Peek		
HS-AS061-M8	M8 x 1.25 Male	M8 x 1.25 Female Peek		
HS-AS061-M8X1.25	M8 x 1.00 Male	M8 x 1.25 Female Peek		
HS-AS061-M10	M10 x 1.5 Male	M10 x 1.5 Female Peek		
HS-AS061-M10X1.25	M10 x 1.25 x 10mm Male	M10 x 1.25 Female Peek		



www.ie-central.com

We reserve the right to alter the specification of this product without prior notice
TS1443U

