

HS-173R Premium Triaxial Accelerometer


Three AC outputs via PUR cable

Key Features

- Output via three axes
- For use with data collector
- Customisable features

Industries

Building services, Pulp and Paper, Mining, Metals, Utilities, Automotive, Water, Pharmaceutical



Technical Performance

Mounted Base Resonance	see 'How To Order' table (nominal) +3kHz for aluminium version
Sensitivity	see: 'How To Order' table $\pm 10\%$ Nominal 80Hz at 72°F per axes
Frequency Response	120cpm (2Hz) to 600kcpm (10kHz) $\pm 5\%$ 90cpm (1.5Hz) to 720kcpm (12kHz) $\pm 10\%$ 48cpm (0.8Hz) to 900kcpm (15kHz) $\pm 3\text{dB}$
Isolation	Base isolated
Range	see: 'How To Order' table
Transverse Sensitivity	Less than 5%

Mechanical

Case Material	Stainless Steel unless specified Aluminium
Sensing Element/Construction	PZT/Shear
Mounting Torque	5.9ft. lbs
Weight	6.8 oz. (nominal)
Maximum Cable Length	3,280 ft.
Standard Cable Length	16 ft.
Screened Cable	PUR - length to be specified with order
Mounting Threads	see: 'How To Order' table
Submersible Depth	328 ft. max (10 bar)


Electrical

Electrical Noise	0.1mg max
Current Range	0.5mA to 8mA
Bias Voltage	10 - 12 Volts DC
Settling Time	1 second
Output Impedance	200 Ohms max.
Case Isolation	$>10^8$ Ohms at 500 Volts

Environmental

Operating Temperature Range	-22 to 194°F
Sealing	IP68
Maximum Shock	5000g
EMC	EN61326-1:2013


Typical Frequency Response (at 100mV/g)



Applications

Fans, Motors, Pumps, Compressors, Centrifuges, Conveyors, Air Handlers, Gearboxes, Rolls, Dryers, Presses, Cooling, VAC, Spindles, Machine Tooling, Process Equipment

Vibration sensor should be firmly fixed to a flat surface (spot face surface may be needed to be produced and cable anchored to sensor body.)



How To Order

Product Prefix HS - Hansford Sensors	Product Series 173 - Triaxial Industrial Vibration Sensor										
	H	S	1	7	3	R	X	X	X	X	X
Extra Options (if required) R - Round Design	Sensitivity		Range		Resonant Frequency		Cable/Connector		Mounting Threads		
	010 - 10mV/g		$\pm 800\text{g}$		1,200kcpm (20kHz)		01 - PUR		02 - ¼-28" UNF Male		
	030 - 30mV/g		$\pm 250\text{g}$		1,140kcpm (19kHz)				06 - M6 x 1mm Male		
	050 - 50mV/g		$\pm 160\text{g}$		1,080kcpm (18kHz)				08 - M8 x 1.25mm Male		
	100 - 100mV/g		$\pm 80\text{g}$		1,020kcpm (17kHz)						
	250 - 250mV/g		$\pm 32\text{g}$		960kcpm (16kHz)						
	500 - 500mV/g		$\pm 16\text{g}$		900kcpm (15kHz)						



www.ie-central.com

We reserve the right to alter the specification of this product without prior notice

TS1456U

